

Upínač Weldon s chladícími kanály pro upínací stopky

Upínač Weldon DIN 6359 pro upínací stopky DIN 1835-B



Název	Kužel	d	D	A		G 2,5 25.000 min ⁻¹
BT40.50.WK.06.ADB	BT40	6	25	63	AD/B	•
BT40.50.WK.08.ADB	BT40	8	28	63	AD/B	•
BT40.63.WK.10.ADB	BT40	10	35	63	AD/B	•
BT40.63.WK.12.ADB	BT40	12	42	80	AD/B	•
BT40.63.WK.14.ADB	BT40	14	44	80	AD/B	•
BT40.63.WK.16.ADB	BT40	16	48	80	AD/B	•
BT40.63.WK.18.ADB	BT40	18	50	80	AD/B	•
BT40.63.WK.20.ADB	BT40	20	52	80	AD/B	•
BT40.90.WK.25.ADB	BT40	25	65	100	AD/B	•
BT40.100.WK.32.ADB	BT40	32	72	105	AD/B	•
BT40.120.WK.40.ADB	BT40	40	80	110	AD/B	•
BT40.100.WK.06.ADB	BT40	6	25	100	AD/B	•
BT40.100.WK.08.ADB	BT40	8	28	100	AD/B	•
BT40.100.WK.10.ADB	BT40	10	35	100	AD/B	•
BT40.100.WK.12.ADB	BT40	12	42	100	AD/B	•
BT40.100.WK.14.ADB	BT40	14	44	100	AD/B	•
BT40.100.WK.16.ADB	BT40	16	48	100	AD/B	•
BT40.100.WK.18.ADB	BT40	18	50	100	AD/B	•
BT40.100.WK.20.ADB	BT40	20	52	100	AD/B	•
BT50.63.WK.06.ADB	BT50	6	25	63	AD/B	•
BT50.63.WK.08.ADB	BT50	8	28	63	AD/B	•
BT50.63.WK.10.ADB	BT50	10	35	63	AD/B	•
BT50.80.WK.12.ADB	BT50	12	42	80	AD/B	•
BT50.80.WK.14.ADB	BT50	14	44	80	AD/B	•
BT50.80.WK.16.ADB	BT50	16	48	80	AD/B	•
BT50.80.WK.18.ADB	BT50	18	50	80	AD/B	•
BT50.80.WK.20.ADB	BT50	20	52	80	AD/B	•
BT50.100.WK.25.ADB	BT50	25	65	100	AD/B	•
BT50.105.WK.32.ADB	BT50	32	72	105	AD/B	•
BT50.110.WK.40.ADB	BT50	40	80	110	AD/B	•

od průměr d = 25 se dvěma upínacími šrouby

d = 6 až 18 se dvěma chladicími kanály

d = 20 až 40 se čtyřmi chladicími kanály