


Upínač Whistle Notch pro upínací stopky

Upínač Whistle Notch DIN 6359 pro upínací stopky DIN 1835-E



Název	Kužel	d	D	A	G 2,5 25.000 min ⁻¹
HSK63A.80.WN.06	HSK63A	6	25	80	•
HSK63A.80.WN.08	HSK63A	8	28	80	•
HSK63A.80.WN.10	HSK63A	10	35	80	•
HSK63A.90.WN.12	HSK63A	12	42	90	•
HSK63A.90.WN.14	HSK63A	14	44	90	•
HSK63A.100.WN.16	HSK63A	16	48	100	•
HSK63A.100.WN.18	HSK63A	18	50	100	•
HSK63A.100.WN.20	HSK63A	20	52	100	•
HSK63A.110.WN.25	HSK63A	25	65	110	•
HSK63A.110.WN.32	HSK63A	32	72	110	•
HSK100A.90.WN.06	HSK100A	6	25	90	•
HSK100A.90.WN.08	HSK100A	8	28	90	•
HSK100A.90.WN.10	HSK100A	10	35	90	•
HSK100A.100.WN.12	HSK100A	12	42	100	•
HSK100A.100.WN.14	HSK100A	14	44	100	•
HSK100A.100.WN.16	HSK100A	16	48	100	•
HSK100A.100.WN.18	HSK100A	18	50	100	•
HSK100A.110.WN.20	HSK100A	20	52	110	•
HSK100A.120.WN.25	HSK100A	25	65	120	•
HSK100A.120.WN.32	HSK100A	32	72	120	•
HSK100A.120.WN.40	HSK100A	40	80	120	•

od průměr d = 25 se dvěma upínacími šrouby