



# Tažné čepy DIN 69872 A+B



provedení A



provedení B



## provedení A - vrtaný bez „0“ kroužku

Název	M	l <sub>1</sub>	l <sub>2</sub>	l <sub>3</sub>	d <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>
69872.M12.K	M12	44	24	19	13	9	13	3,0
69872.M16.K	M16	54	26	20	19	14	17	7,0
69872.M24.K	M24	74	34	25	28	21	25	11,5

## provedení A - vrtaný s „0“ kroužkem

69872.M16.KO	M16	54	26	20	19	14	17	7,0
69872.M24.KO	M24	74	34	25	28	21	25	11,5

## provedení B - nevrtaný s „0“ kroužkem

69872.M16.O	M16	54	26	20	19	14	17	-
69872.M24.O	M24	74	34	25	28	21	25	-

## DIN 69872 A | prodloužený + 3 mm



provedení A



## provedení A - vrtaný s „0“ kroužkem

Název	M	l <sub>1</sub>	l <sub>2</sub>	l <sub>3</sub>	d <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>
69872.M16.KO.3	M16	54	26	20	19	14	17	7,0