



Tažné čepy JIS B 6339 (MAS 403 BT)



nevrtaný bez „0“ kroužku

Název	M	α	l_1	l_2	l_3	d_1	d_2	d_3
6339.M12.45	M12	45°	43	23	18	11	7	12,5
6339.M12.60	M12	60°	43	23	18	11	7	12,5
6339.M16.45	M16	45°	60	35	28	15	10	17,0
6339.M16.60	M16	60°	60	35	28	15	10	17,0
6339.M16.90	M16	90°	60	35	28	15	10	17,0
6339.M24.45	M24	45°	85	45	35	23	17	25,0
6339.M24.60	M24	60°	85	45	35	23	17	25,0
6339.M24.90	M24	90°	85	45	35	23	17	25,0



vrtaný s „0“ kroužkem

Název	M	α	l_1	l_2	l_3	d_1	d_2	d_3	d_4
6339.M12.45.K0	M12	45°	43	23	18	11	7	12,5	2,5
6339.M12.60.K0	M12	60°	43	23	18	11	7	12,5	2,5
6339.M16.45.K0	M16	45°	60	35	28	15	10	17	4,0
6339.M16.60.K0	M16	60°	60	35	28	15	10	17	4,0
6339.M16.90.K0	M16	90°	60	35	28	15	10	17	4,0
6339.M24.45.K0	M24	45°	85	45	35	23	17	25	6,0
6339.M24.60.K0	M24	60°	85	45	35	23	17	25	6,0
6339.M24.90.K0	M24	90°	85	45	35	23	17	25	6,0