

## Accessories

item	Model	HSA-2212	HSA-X20	HSA-X23	HSA-X27	HSA-X28	HSA-X32	HSA-X36
1.Full Enclosed Splash Guard _Multi-piece Door		●	●	●	●	●	●	●
2.Spindle Air Curtain		●	●	●	●	●	●	●
3.Air Blast Through Spindle		●	●	●	●	●	●	●
4.Table Side Air Blast (1 tube)		●	●	●	●	●	●	●
5.Lubrication system		●	●	●	●	●	●	●
6.Fluorescent lampx1		●	●	●	●	●	●	●
7.Spindle Cooler		●	●	●	●	●	●	●
8.Foundation bolt, Concrete		●	●	●	●	●	●	●
9.Portable Chip Bucket		●	●	●	●	●	●	●
10.Screw Type Chip Conveyer		●	●	●	●	●	●	●
11.Oil Fluid Separator		★	★	★	★	★	★	★
12.Cooling System		★	★	★	★	★	★	★
13.Tools package		●	●	●	●	●	●	●
14.Hartford Manual x1		●	●	●	●	●	●	●
15.Auto Power off		●	●	●	●	●	●	●
16.Operation Finish Lamp		●	●	●	●	●	●	●
17.Foot Switch For Spindle Clamp/Unclamp		●	●	●	●	●	●	●
18.Remote Manual Pulse Generator		●	●	●	●	●	●	●
19.RS232 Interface		●	●	●	●	●	●	●
20.Convection Heat Exchanger in Control Box		●	●	●	●	●	●	●
21.Armsless Type Tool Magazine(20 pcs)	-	●	●	●	●	●	●	●
22.6000 rpm Gear Spindle		●	●	●	●	●	●	●
23.CTS Full splash guard with top cover		★	★	★	★	★	★	★
24.Fluorescent Lamp x2		★	★	★	★	★	★	★
25.Link Type Chip Conveyor & Portable Chip Bucket(1 EA)		★	★	★	★	★	★	★
26.Coolant Through Spindle, 20BAR, with Secondary tank		★	★	★	★	★	★	★
27.Coolant Through Spindle, 25BAR, with Secondary Tank		★	★	★	★	★	★	★
28.Hydraulic Hose Coolant gun		★	★	★	★	★	★	★
29.Air Gun		★	★	★	★	★	★	★
30.Hartford Manual x2/3		★	★	★	★	★	★	★
31.X/Y/Z-axis linear scale system_HEIDENHAIN		★	★	★	★	★	★	★
32.Without Tool Magazine		★	★	★	★	★	★	★
33.Tool ARM Type Tool Magazine		★	★	★	★	★	★	★
34.10000/12000 rpmDirect Drive Spindle		★	★	★	★	★	★	★
35.NC Rotary Table		★	★	★	★	★	★	★
36.Angular Head(HF-M90L)		★	★	★	★	★	★	★
37.Extend Head (Hartford)		★	★	★	★	★	★	★
38.Multangular Milling Head (HF-MU360L)		★	★	★	★	★	★	★
39.Semi-Automatic Angular Head ((HF-S90L)		★	★	★	★	★	★	★
40.Semi-Automatic Multangular Milling Head (HF-SU360L)		★	★	★	★	★	★	★
41.Automatic Angular Head(G.Y)		★	★	★	★	★	★	★
42.Extend Head (GY-E73N or GY-E75N)		★	★	★	★	★	★	★
43.Auto Tool Length Measurement		★	★	★	★	★	★	★
44.Imitative Mold Cutting System		★	★	★	★	★	★	★
45.Speed Increaser		★	★	★	★	★	★	★
46.DNC Software		★	★	★	★	★	★	★

## Electrical features Standard equipment & optional features

### Hartrol / standard equipment

- Manual workpiece alignment
- Tool magazine graphics and data display
- Pop-up computer
- Supporting processing parameters
- Lettering processing function
- Tool correction screen & fast tool change function((only suitable for Fanuc))

### Hartnet / Optional features

- Whole plant utilization rate management system
- Processing countdown management
- Whole plant file transfer system
- Output management

### Electrical function / Optional features

- Machine utilization rate analysis (only suitable for Fanuc)
- Internal and external thread cutting (only suitable for Fanuc)
- Tool magazine data display-Tool style graphical data display (only suitable for Fanuc)
- Tool life monitoring((only suitable for Fanuc))
- Power-off gravity axis lift function
- Coordinate display hand input
- Tool magazine HMI
- Rigid tapping tool retraction
- Spindle thermal displacement compensation

**She Hong INDUSTRIAL CO. LTD.**

No.3 Jingke N. Road, Taichung City, 408 Taiwan

www.hartford.com.tw Tel: 886-4-23501980 Fax: 886-4-23581793

CAT.No.: 20231113-E09

All Graphic and text on the catalog have been registered. Those who reprint will be held liable

Standard : ●  
Optional : ★

**Hartford**  
EXCLUSIVE  
HartfordPlus App

# Intelligent Double Column Machining Center

Software machine

HSA Series

- Hartrol premium controller
- 5-year warranty on guideways
- Gear type 8,000rpm spindle
- Four linear guideways on Z-axis



AI. Applications inside, Hartrol Premium is the control which provides machining status with advanced features.

## AI SmartControl




Major functions  
of Hartford AI  
controller



Imagine what future machines  
ought to be outlined.

## Hartford redefine the future



1  
IoT  
+ Hartrol Premium Sync & Update  
+ User Connect



2  
Thermal stability solution  
+ Spindle Thermal Compensation  
+ Casting Thermal Compensation  
+ Thermal Symmetry / Thermal Balancing



3  
ZDT  
+ Diagnosis Report on Spindle Operation  
+ Alarm Report System



4  
AI  
+ Facial Recognition System  
+ AI Efficient Lubrication Management  
+ Smart Efficient Chip Collection



# The very first step for fully intelligent machining.

## What is Hartrol Premium?

Hartrol premium is a brand new intelligent controller Hartrol , Hartnet and Hartford electrical function together which developed and made by Hartford.

HMI and operation is user friendly, it can achieve :

1. Internet connection, collect and analyze data, monitoring by portable device
2. Intelligent control: Auto revise human error and operating basis
3. Real time update new APPs

The difference between Hartrol plus and others

Function	Hartrol Premium	Others
Screen Size	19" Multi-touch Panel	10.4" (OPT:15")
Look Ahead Block	2700(G5P20000)	400(1000 Max.)
Hard Drive	32GB SSD	NO
Smoothing Interpolation	SSS 4G	Option
Industry 4.0	Hartford UserConnect	NO



## The Intelligent Controller You Should Have

With three major solutions, Hartrol Premium takes you machining to the next level.

Highly optimized and intelligent controls bring even more capabilities and productivity to your metal cutting processes.

With ease use, advanced automation, and smart data collection, Hartrol plus is essential tool for enhancing performance on your production floor.

### Cost down to 20%

Multi Touch Screen  
CCD remote management  
E-book  
Remote Management  
Cutting Condition Calculator  
Stand-by Mode

### Intelligent Support

### Productivity increased 23%

HartCAM  
AFC= Automatic Feedrate Control.  
SSS-4G  
Machining Time Countdown for Single Block  
Optimized Machining Program  
Automatic measurement

### Hartrol Premium

### Intelligent Functions

MES (Manufacturing Execution System)  
Machine Utilization Management  
Operator Performance Management  
24 Hours a Day Management  
Remote Management  
Hartford Userconnect

### Efficiency increased 20%

### Hartford UserConnect

- Alert Notification
- Remote Diagnoses
- Remote Value Enhancement
- Remote Monitoring & Management

## Hartford APP Store

The main technologies of Hartford smartcenter include intelligent managing system, status monitoring, alarm predicting, machine status diagnosis, crash preventing, 3D program simulation, machining efficiency improving...etc.  
All the intelligent functions help you control the machine status and assure the job quality.



### Hartford smartcenter APP



The functions mentioned above will need to option the Hartrol premium controller or Dual screen with Fanuc controller.

### AI Tool breakage detection (opt.)

Available with tool size 6mm above

- Tool wears when electric current ratio increased
- When tool abrasion over than your setting, machine alarms to avoid tool breakage



### Highlight on Intelligent Auger(opt.)

50% efficiency increases

- Intelligent auger automatically proceeds cleaning iron chips based on electrical current of spindle.
- Intelligent auger automatically performing reversal mode in case amount of iron chips outnumbers, preventing from machine stop.
- Auger is overly shielded



## What Hartford APP can do for you?

### AI Environment Thermal Displacement Compensation(opt.)

Vertical machining center : **0.03mm**  
Thermal displacement problem is improved up to **60%**  
It can achieve good accuracy as in constant temperature room.



### AI Efficient Lubrication Management (opt.)

**50%** lubrication saved.  
■ Auto-adjustment oil supply base on machining condition.  
■ 50% oil consumption saved



### AI Facial recognition system (opt.)

Face ID log-in authority  
Recognition time: **2 seconds**  
Recognition accuracy: **100%**



### Hartford ZDT

Eliminate machine down time and increase efficiency.  
ZDT –  
1.Ease of use  
2.Check parts status clearly  
3.Eliminating unexpected down time  
4.Instant notification to your machine and your portable device



### Spindle Vibration Intelligent Monitoring System (B-Safe) is ensuring spindle stability at times(opt.)

- Highlights**
- APP Vibration function is handy to set up manually.
  - Alert status on crash protection.
  - Responsive graphic is available for diagnosis by user, and analytic information is just-in-time served.



Strong cutting force; release your production potential

All New Infinity of high rigidity, high-precision can help you machine blank to become the finished mold of excellent precision and smoothness.



Table of vertical machining center



column of vertical machining center

## Actual Cutting Test

Model: HSA-428


■ Spindle: 6,000 rpm Gear type, 26kW ■ Cutting material : S45C

<b>Face milling</b> Tool diameter Ø125 mm Feed rate 2,050 mm/min Cutting depth 4 mm Cutting width 100 mm Cutting volume 820 cc/min	<b>End milling</b> Tool diameter Ø63 mm Feed rate 1,350mm/min Cutting depth 40 mm Cutting width 10 mm Cutting volume 540 cc/min	<b>Tapping</b> Tool diameter M36 x P4 mm Feed rate 480 mm/min Cutting depth 40 mm Spindle speed 120rpm	<b>Drilling</b> Tool diameter Ø53 mm Feed rate 100mm/min Cutting depth 50 mm Spindle speed 400rpm

All the test results featured in this catalogue were produced under strict testing condition in a special zed testing environment. Under different testing conditions and in less than ideal testing environments, the test results may vary from those shown in this catalogue.

## ALL NEW INFINITY, from roughing to finishing, allows you to accomplish at one go

The brand-new HSA series brings you the best processing performance and ultimate precision. At the same time, it incorporates a self-developed manual head-changing mechanism with the HSA architecture, achieving a five-axis machining model. This unique machine structure design caters to various types of processing needs.



### Full range of linear guideway five-year warranty

Warranty coverage will not apply under following conditions

- 1.Improper operation(collision)
- 2.Lack of regular cleaningof accumulated debris causing damage to the linear rails &carriages.




### Z-axis four linear guideways three binding structure patented technology

The patented HSA four linear guideways three binding structure technology, two-way support provides high rigidity while cutting, bringing you excellent performance. Patent No.1264343 machining center Z-axis head Z-axis four linear guideways.



### HSA three-axis direct-connected drive advantage

HSA series X-axis and Y-axis pair up with the planetary reducer, effectively enhancing the overall axial drive torque of the machine.



### X-axis three linear guideways design

HSA-X28/HSA-X32/HSA-X36

The X-axis three linear guideways design can be used to resist process rotation torsion and enhance rigidity by more than **50%**. Moreover, the maximum load of a workbench can be **30,000kg**, thus allowing you to meet your processing needs and help you each your accuracy and quality requirements.



( HSA-X20 / X23 / X27 / X212 are two linear guideways.)

# Unique Machine Structure Design


## Screw support mechanism maintains excellent positioning accuracy

- In time of the transmission of the X and Y axes, ensure that power is maintained.
- Improve screw dead weight sagging; enhance the positioning accuracy and life of screw.


Model above the 5 meters X-axis is standard configuration; below 4 meters is optional configuration.

Y-axis support mechanism, X36 is standard configuration.

Y-axis support mechanism, X23/X27/X28 is optional configuration.



X-axis screw support mechanism



Y-axis screw support mechanism


## Diversified strong spindle meets your processing needs



### Hartford made gear type 8,000 rpm Two-stage spindle (optional feature)

- To follow the process attribute, pair up with high or low gear.
- Spindle-mounted structure design
- Thermal separation technology enables thermal extension to control and apply to HAS-X20 / X23 / X27 / X28 / X32 / X36

◀ Hartford made gear type 8,000 rpm  
Two-stage spindle (optional feature)



### 1.The new slant beam design effectively reduces vibration from cutting

- Reduce the vibration generated by the process.
- Enhance accuracy and surface sheet cleanliness during processing.

Patent :  
M435318 Beam rear slant design

### 2.Extra-large columns effectively transfer the maximum cutting force

- The joint width between bottom of the column and the base is increased to 1,250mm
- Reduce overall vibration from cutting.


Patent:  
M437316 Structure section has design to resist torsion.  
M438938 Column foot span design

### 3.Z-axis nitrogen accumulator weight system(OPT.)

- Reduce operating noise of hydraulic tank.
  - Reduce hydraulic tank oil temperature by 50%
  - Effective energy-saving more than 20%
- Suitable for HSA-X23/X27/X28/X32/X36 full range of models.


## The Y-axis is designed to bring a broader range of processing

ALL NEW INFINITY series models providing increased Y-axis travel design, you can upgrade your range of processing through the increase of Y-axis travel. We have achieved our purpose to process the widest range with the minimum cost.



Model	Z-TRAVEL	COLUMN-HIGH	A	B	C	D		E		F		G		H	I
						M90L	S90L	M90L	S90L	M90L	S90L	M90L	S90L		
HSA-320			3000	2000		2636	2588	1636	1588						
HSA-420			4000	2000		3636	3588	1636	1588						
HSA-323	780	1900	3000	2300	980	2636	2588	1936	1888	602.5	517	743.5	658		
HSA-423	780	2000	4000	2300	1080	3636	3588	1936	1888	702.5	617	843.5	758		
HSA-523	1000	2200	5000	2300	1280	4636	4588	1936	1888	902.5	817	1043.5	958		
HSA-327	1200	2400	3000	2700	1480	2636	2588	2336	2288	1102.5	1017	1243.5	1158	50	141
HSA-427			4000	2700		3636	3588	2336	2288						
HSA-527			5000	2700		4636	4588	2336	2288						
HSA-627			6000	2700		5636	5588	2336	2288						
HSA-428			4000	2800		3636	3588	2436	2388						
HSA-528			5000	2800		4636	4588	2436	2388						
HSA-532	780	2000	5000	3200	1040	4636	4588	2836	2788	662.5	577	803.5	718		
HSA-632	1000	2200	6000	3200	1240	5636	5588	2836	2788	862.5	777	1003.5	918		
HSA-536	1200	2400	5000	3600	1440	4636	4588	3236	3188	1062.5	977	1203.5	1118		
HSA-636			6000	3600		5636	5588	3236	3188						
HSA-736			7000	3600		6636	6588	3236	3188						
HSA-836			8000	3600		7636	7588	3236	3188						

unit : mm







Model	Z-TRAVEL	COLUMN-HIGH	A	B	C	D		E		F		G		H	
						V	H	V	H	V	H	V	H		
HSA-320			3000	2000		3000	2000	2610	2636	1610	1636				
HSA-420			4000	2000		4000	2000	3610	3636	1610	1636				
HSA-323	780	1900	3000	2300	980	3000	2300	2610	2636	1910	1936	511.5	564.5	561.5	743.5
HSA-423	780	2000	4000	2300	1080	4000	2300	3610	3636	1910	1936	611.5	780	661.5	843.5
HSA-523	1000	2200	5000	2300	1280	5000	2300	4610	4636	1910	1936	811.5	864.5	861.5	1043.5
HSA-327	1200	2400	3000	2700	1480	3000	2700	2610	2636	2310	2336	1012	1064.55	1062	1243.5
HSA-427			4000	2700		4000	2700	3610	3636	2310	2336				
HSA-527			5000	2700		5000	2700	4610	4636	2310	2336				
HSA-627			6000	2700		6000	2700	5610	5636	2310	2336				
HSA-428			4000	2800		4000	2800	3610	3636	2410	2436				
HSA-528			5000	2800		5000	2800	4610	4636	2410	2436	571.5	624.5	621.5	803.5
HSA-532	780	2000	5000	3200	1040	5000	3200	4610	4636	2810	2836	771.5	824.5	821.5	1003.5
HSA-632	1000	2200	6000	3200	1240	6000	3200	5610	5636	2810	2836	971.5	1024.5	1022	1203.5
HSA-536	1200	2400	5000	3600	1440	5000	3600	4610	4636	3210	3236				
HSA-636			6000	3600		6000	3600	5610	5636	3210	3236				
HSA-736			7000	3600		7000	3600	6610	6636	3210	3236				
HSA-836			8000	3600		8000	3600	7610	7636	3210	3236				

unit : mm

12

The Y-axis is designed to bring a broader range of processing



Module	Z-TRAVEL	COLUMN-HIGH	A			B		C		D		E		F		G		H	
			V	H	V	V	H	V	H	V	H	V	H	V	H	V	H	V	H
HSA-320			3000	2000		2480	2588	1480	1588										
HSA-420			4000	2000		3480	3588	1480	1588										
HSA-323	780	1900	3000	2300	980	2480	2588	1780	1888	416	472	466	672						
HSA-423	780	2000	4000	2300	1080	3480	3588	1780	1888	516	572	566	772						
HSA-523	1000	2200	5000	2300	1280	4480	4588	1780	1888	716	772	766	972						
HSA-327	1200	2400	3000	2700	1480	2480	2588	2180	2288	916	972	966	1172						
HSA-427			4000	2700		3480	3588	2180	2288										
HSA-527			5000	2700		4480	4588	2180	2288										
HSA-627			6000	2700		5480	5588	2180	2288			50	50						
HSA-428			4000	2800		3480	3588	2280	2388										
HSA-528	780	2000	5000	2800	1040	4480	4588	2280	2388	476	532	526	732						
HSA-532	1000	2200	5000	3200	1240	4480	4588	2680	2788	676	732	726	932						
HSA-632	1200	2400	6000	3200	1440	5480	5588	2680	2788	876	932	926	1132						
HSA-536			5000	3600		4480	4588	3080	3188										
HSA-636			6000	3600		5480	5588	3080	3188										
HSA-736			7000	3600		6480	6588	3080	3188										
HSA-836			8000	3600		7480	7588	3080	3188										


unit : mm

Module	Z-TRAVEL	COLUMN-HIGH	A		B		C		D		E		F			
			ME35L	ME50L												
HSA-320			3000	2000												
HSA-420			4000	2000												
HSA-323	780	1900	3000	2300	980											
HSA-423	780	2000	4000	2300	1080											
HSA-523	1000	2200	5000	2300	1280											
HSA-327	1200	2400	3000	2700	1480											
HSA-427			4000	2700												
HSA-527			5000	2700												
HSA-627			6000	2700												
HSA-428			4000	2800												
HSA-528	780	2000	5000	2800	1040											
HSA-532	1000	2200	5000	3200	1240											
HSA-632	1200	2400	6000	3200	1440											
HSA-536			5000	3600		4480	4588	3080	3188							
HSA-636			6000	3600		5480	5588	3080	3188							
HSA-736			7000	3600		6480	6588	3080	3188							
HSA-836			8000	3600		7480	7588	3080	3188							

unit : mm

14

The Y-axis is designed to bring a broader range of processing




GYAutomatic 90 degree head \_N75

Module	Z-TRAVEL	COLUMN - HIGH	A	B	C	D	E	F	G	H
HSA-320			3000	2000		2636	1636			
HSA-420			4000	2000		3636	1636			
HSA-323	780	1900	3000	2300	980	2636	1936	543	678	
HSA-423	780	2000	4000	2300	1080	3636	1936	643	778	
HSA-523	1000	2200	5000	2300	1280	4636	1936	843	978	
HSA-327	1200	2400	3000	2700	1480	2636	2336	1043	1178	
HSA-427			4000	2700		3636	2336			
HSA-527			5000	2700		4636	2336			
HSA-627			6000	2700		5636	2336			
HSA-428			4000	2800		3636	2436			
HSA-528	780	2000	5000	2800	1040	4636	2436	603	738	
HSA-532	1000	2200	5000	3200	1240	4636	2836	803	938	
HSA-632	1200	2400	6000	3200	1440	5636	2836	1003	1138	
HSA-536			5000	3600		4636	3236			
HSA-636			6000	3600		5636	3236			
HSA-736			7000	3600		6636	3236			
HSA-836			8000	3600		7636	3236			

unit : mm

QC cutting ability test present the beat quality of Hartford



#### HSA-423 Mold Testing

- Test materials : F25C
- Cutting speed : F200-500
- Spindle speed : S500-800
- Test tool diameter : ø25mm

#### Positioning machining precision

##### Positioning accuracy

	A	B	C	D	K
Error value	0.020	0.020	0.020	0.020	0.015
Actual value	0.0016 (⊕)	0.0015 (⊕)	0.0070 (⊕)	0.0019 (⊕)	0.0037 (○)

unit(mm)

#### Through FIG cutting accuracy

##### Precision through FIG.

Accuracy	Error value	The actual value
The true flatness of bed top surface(X/Y-axis)	1000 ▼ 0.05/M, 1000-2000 ▲ 0.06/M, 2000 0.07/M	0.02
Right angle of mutual movement of each axis(X/Y-axis)	0.020/500	0.005
Right angle of mutual movement of each axis(Y/Z-axis)	0.02/500	0.005
Slanting swing in spindle hole	Fixed Side : 0.005, Free Side : 0.015/300	0.001/0.005
Accuracy through roundness	0.012/150(X-axis 5000以上 0.020/150)	0.003

2.Manual position head (manually fixed) applicable to general model HSA



Universal head (manual/semi-automatic)		Manual universal head	Semi-automatic universal head
A-axis : ±110°, C-axis : ±180°	Binding mechanism	Manual	Manual
Maximum speed:2,500rpm	Unclamping mechanism	Manual	Automatic
Maximum power:18.5kw	C-axis rotation	Manual	Manual



90° side milling head (manual/ semi-automatic)		Manual 90° head	Semiautomatic 90° head
Manual tool change(manual / hydraulic lock release tool.)	Binding mechanism	Manual	Manual
Maximum speed:2,000rpm	Unclamping mechanism	Manual	Automatic
Maximum power:18.5kW	C-axis rotation	Manual	Manual




Extension head (350/500mm)		Maximum speed : 4.000rpm
		Maximum power : 18.5kW
		The maximum torque to withstand : 650N·m

# A variety of Hartford made spindles have Quality assurance



## Torque curve diagram

- 6,000 rpm gear type spindle
- 8,000 rpm gear type spindle(optional configuration)
- 12,000 rpm direct-connected spindle(optional configuration)


### Direct type




### Gear type 6,000RPM



### Gear type 8,000RPM




## Machine Dimension



HSA-X20/X23/X27/X28/X32/X36 Series

Model	A	B	C	C1	C2	D	E	E1	E2	F	G	H	I	J
HSA-320	9078	4955	4800/4900	5300	5700	8796	1900/2000	2200	2400	2125	2185	4394	2194	1630
HSA-420	11078	4955	4800/4900	5300	5700	10796	1900/2000	2200	2400	2125	2185	4394	2194	1630
HSA-323	9078	5255	4800/4900	5300	5700	8796	1900/2000	2200	2400	2200	2260	4579	2494	1630
HSA-423	11078	5255	4800/4900	5300	5700	10796	1900/2000	2200	2400	2200	2260	4579	2494	1630
HSA-523	13078	5255	4800/4900	5300	5700	12796	1900/2000	2200	2400	2200	2260	4579	2494	1630
HSA-327	9000	5840	4800/4900	5300	5700	8795	1900/2000	2200	2400	2525	2585	5195	2994	1630
HSA-427	11000	5840	4800/4900	5300	5700	10795	1900/2000	2200	2400	2525	2585	5195	2994	1630
HSA-527	13000	5840	4800/4900	5300	5700	12795	1900/2000	2200	2400	2525	2585	5195	2994	1630
HSA-627	15200	5840	4800/4900	5300	5700	14995	1900/2000	2200	2400	2525	2585	5195	2994	1630
HSA-428	11000	5840	4900	5300	5700	10795	2000	2200	2400	2525	2585	5195	2994	1630
HSA-528	13000	5840	4900	5300	5700	12795	2000	2200	2400	2525	2585	5195	2994	1630
HSA-532	13000	6240	4900	5300	5700	12795	2000	2200	2400	2750	2810	5670	3394	1630
HSA-632	15200	6240	4900	5300	5700	14995	2000	2200	2400	2750	2810	5670	3394	1630
HSA-536	13150	6740	4900	5300	5700	12945	2000	2200	2400	3025	3085	6195	3794	1730
HSA-636	15350	6740	4900	5300	5700	15145	2000	2200	2400	3025	3085	6195	3794	1730
HSA-736	17350	6740	4900	5300	5700	17145	2000	2200	2400	3025	3085	6195	3794	1730
HSA-836	19350	6740	4900	5300	5700	19145	2000	2200	2400	3025	3085	6195	3794	1730



HSA-2212

Model	A	B	C	C1	D	E	F	G	H	I	J
HSA-2212	6800	3855	4120	4320	6355	1700	1423.5	1193.5	2832.5	1480	1425

unit : mm

HSA-X16

Model	A	B	C	C1	C2	C3	D	E	F	G	H	I	J
HSA-216	6682	4063	4338	4438	4538	5038	6266	1750	1733.5	1458.5	3379.5	1820	1413
HSA-316	9040	4063	4338	4438	4538	5038	8624	1750	1733.5	1458.5	3379.5	1820	1413

unit : mm

# Mechanical Specifications Table

Item	Model Unit	HSA-2212	HSA-216 / 316	HSA-320 / 420	HSA-323/423/523	HSA-327/427/527/627	HSA-428/528	HSA-532/632	HSA-536/636/736/836
Table	Working surface mm	2000 x1100	2000 / 3000 x1400	3000 / 4000 x1800	3000 / 4000 / 5000x 2200	3000 / 4000 / 5000 / 6000x 2200	4000 / 5000 x2500	5000 / 6000 / 7000 / 8000x 3000	
	T-slot Width X pitch(number) mm	22 x160 (6)	22 x 180 (7)	22 x 250 (11 / 15)	28 x 250 (11 / 15 / 19)	28 x 250 (11 / 15 / 19 / 23)	28 x 250 (15 / 19)	28 x 250 (19 / 23 / 27 / 31)	
	Max. load (Average) kg	3500	8000 / 10000	10000 / 12000	10000 / 12000 / 15000	10000 / 12000 / 15000 / 18000	18000 / 20000	20000 / 23000	
	X-axis travel mm	2250	2250 / 3250	3000 / 4000	3000 / 4000 / 5000	3000 / 4000 / 5000 / 6000	4000 / 5000	5000 / 6000	
	Y-axis travel mm	1200	1600 ; 1500(opt. for Z-axis box guideway)	2000	2300	2700	2800	3200	
	Z-axis travel mm	780	780	780 opt. 1000/1200	780 opt. 1000/1200	780 opt. 1000/1200	780 opt. 1000/1200	780 opt. 1000/1200	
	Distance from spindle center to column mm	450	430	450	450	450	450	450	
	Distance between two columns mm	1300	1600	2000	2300	2800	2800	3200	
	Distance from Spindle End to Table#50 mm	7780:120~900 Z1000:140~1140	2780:200~980 Z1000 : 280 ~1280 Z1200 : 280 ~1480	2780 : 260 ~1040 Z1000 : 340 ~1340 Z1200 : 340 ~1540	2780 : 260~1040 Z1000 : 280~1280 Z1200 : 280~1480	2780:260~1040 Z1000:240~1240 Z1200:240~1440	2780:260~1040 Z1000:240~1240 Z1200:240~1440	2780:260~1040 Z1000:240~1240 Z1200:240~1440	
	Distance from Spindle End to Table#40 mm	Z780:180~960	Z780:220~1000	#40 / #50	#40 / #50	#50	#50	#50	
Spindle	Spindle nose taper	#40/#50	#40 /#50	#40 10000/15000/20000 #50 10000/12000	#40 15000 / 20000 #50 10000 / 12000	10000 / 12000	10000 / 12000	10000 / 12000	
	Spindle speed(DDoS) rpm	10000 opt.15000 only on #40		#50 6000 / 8000	#50 6000 / 8000	6000 / 8000	6000 / 8000	6000 / 8000	
	Spindle speed(Gear) rpm	6000 only on #50 opt. 8000		#50 12000	#50 12000	12000	12000	12000	
	Spindle speed(Built-In) rpm	-	-						
Feed	Cutting feedrate m/min (X / Y / Z)	10/10/10	12/12/12 ; 12/12/7 (opt. for Z-axis box guideway)	12/12/12	12/12/12 (323) 10/12/12(423) 8/12/12(523)	12/12/12(327) 10/12/12(427) 8/12/12 ( 527 / 627 )	10/12/16(327/427) 14/18/16 ( 527 ) 10/18/16 ( 627 )	8/12/12 ( 532 / 632 )	
	Rapid traverse rate m/min (X / Y / Z)	24/24/20	24/24/20 24/24/15 (opt. for Z-axis box guideway)	20/18/16	20/18/16 (323/423) 14/18/16 (523)	20/18/16 (327/427) 14/18/16 ( 527 ) 10/18/16 ( 627 )	16 / 18 / 16 (428) 12 / 18 / 16 ( 528 )	8/10/10 (526/636/736) 6/10/10 (836)	
	Capacity pcs	A: 24 opt. 32/40 only on #50	#40 A:32(40) : #50 A:32(40/60) S:20	A: 32 / 40 / 60	A: 32 (40 / 60)	A: 32 / 40 / 60	A: 32 / 40 / 60	A: 32 / 40 / 60	
ATC	Max. tool weight kg	#40: 7 #50: 18	#40: 7 #50: 18	#40 A: 7 #50 A: 20	#40 : 7 #50 : 20	A: 20	A: 20	A: 20	
	Tool shank	BT50(BBT40/BBT50/CAT40/CAT50/DIN)	BT-50 (CAT50/DIN/BBT50) BT-40 (CAT50/DIN/BBT40/HSK-A63)	#40 BT-40(CAT40/DIN/BBT40/HSK-A63) #50 BT-50(CAT50/DIN/BBT50)	#40 BT40(BBT40)/CAT40(DIN69871A) #50 BT50(BBT50)/CAT50(DIN69871A); HSKA63 (#40)	BT-50(BBT-50/CAT-50/DIN69871A)	BT-50(BBT-50/CAT-50/DIN69871A)	12/18/16(532)	
	Pull stub bolt	P50T-1/CAT-50/DIN, MAS-P40T-1/CAT-40/DIN	P40T-1 / P50T-1 (CAT-40/DIN 69872)	#40 P40T-1 #50 P50T-1	#40 MAS-P40T-1/DIN69872A(PD40TA) #50 MAS-P50T-1/DIN69872A(PD50TA)	MAS-P50T-1/DIN69872A(PD50TA)	MAS-P50T-1 / DIN69872A(PD50TA)	MAS-P50T-1 / DIN69872A(PD50TA)	
	Max. tool size(dia.X length) #40 mm	75 x 300	Ø 75x 300L	A: Ø 125 x 300L	A: Ø 75 x 300L x 7kg	—	—	—	
Motor	Max. tool size(dia.X length) #50 mm	110 x 350(24T) / 125 x 350(32T/40T)	Ø125 x 300L	A : Ø 125 x 300L	A : Ø 125 x 400L x 20kg	Ø125 x 400L x 20kg	Ø125 x 400L x 20kg	Ø125 x 400L x 20kg	
	Spindle drive motor (cont./30 min) kw	#40:11/7.5 #50:18.5/15(22/26)	#40 : 7.5 / 11 (opt.15/18.5) #50 : 18.5 / 22 opt. 22 / 26, 30 / 37	#40 : 11 / 7.5 DDS for Fanuc #50 : 22/18.5(18.5/15 DDS for Fanuc)	18.5 / 22 (15 / 18.5 DDS)	18.5 / 22 (15 / 18.5 DDS)	18.5 / 22 (15 / 18.5 DDS)	18.5 / 22 (15 / 18.5 DDS)	
	3-axis laser positioning accuracy(JIS B6330), without linear scale								
Positioning Accuracy	Positioning accuracy mm	±0.010	±0.010	±0.010	±0.010 / ±0.012 / ±0.012	±0.012	±0.012	±0.012	
	Repeatability mm	±0.003	±0.003	±0.003	±0.003	±0.003	±0.003	±0.003	
	3-axis laser positioning accuracy(JIS B6330), with linear scale								
	Positioning accuracy mm	±0.008	±0.008	±0.008	±0.008 / ±0.010 / ±0.010	±0.010	±0.010	±0.010	
Positioning Accuracy	Repeatability mm	±0.003	±0.003	±0.003	±0.003	±0.003	±0.003	±0.003	
	3-axis laser positioning accuracy(VDI13441) repeat 5 time								
	Positioning accuracy mm	0.015	0.015 / 0.016	0.016 / 0.018	0.016 / 0.018 / 0.026	0.018 / 0.026	0.026	0.026	
	Repeatability mm	0.014	0.014	0.014 / 0.015	0.014 / 0.015 / 0.021	0.014 / 0.015 / 0.24	0.015 / 0.021	0.021	
Electric power requirement	Required air pressure kg/cm <sup>2</sup>	6.5	6.5	6.5	6.5	6.5	6.5	6.5	
	Electric power requirement kVA	#50 : 35-65 #40 : 25-60	45 / 50	40-70	40 - 75	40 - 75 [ 428 / 528 ]	45 - 70(532) : 45-75(732)	45 - 75	
	Machine weight kg	#50: 14720 #40:14720	18000 / 21000	2780 : 30100 / 34100 / 38100 Z1000 : 31420 / 35420 / 39420 Z1200 : 32000 / 36200 / 40200	2780 : 33370 / 37370 / 45370 Z1000 : 34690 / 38690 / 46690 Z1200 : 35470 / 39470 / 47470	2780 : 39000 / 44000 Z1000 : 39500 / 44500 Z1200 : 40000 / 45000	2780 : 44000 Z1000 : 46500 Z1200 : 47000		
	Floor space mm	8535 x 5745	8630 / 10630 x 5880	11245 / 13245 x 6600	11415 / 13415 / 15415 x 6900	11650/13650/15650/17650 x 7500	13650 / 15650 x 7500	15744 x 7900	
other	Machine dimension (L x W x H) mm	Z780 : 6800 x 3855 x 4120	6712 / 9040 x 4619.5 x 4338(Z780)	9080 / 1080 x 4955x4800(Z780) (Z1000:H5300/Z1200:H5700)	9145 / 11145 / 13145 x 5255 x 4800(Z780)	9077 / 1077 / 13077 / 15077 x 5914.5 x 4796(Z780)	11077 / 13077 x 5610.5 x 4896 (Z780)	2780 : 13105 / 15105 x 6300 x 4896	
								15200 / 17200 / 19200 / 21200 x 8450 Z780 : 13148 / 15148 / 17148 / 19148 x 4651 x 4896	

VDI 3441 accuracy available upon order request.

※ According to standard machine for high precision mold machining industry, Z axis rapid traverse is 12000(mm/min)※