


Vrták V3100 s vyměnitelnou VBD



HLOUBKA VRTÁNÍ 3xD / s vnitřním chlazením



Válcové provedení s ploškou

Objednací číslo	Rozměry (mm)							VBD	Šroubek	Klíč
	D	d	d1	L	L1	L2				
V3100.15.5.V25.D3	15,5	25	34	126	46,5	56	WPMT 033208 (1,2 Nm)	TMSV-M2,5x6	T08	
V3100.16.V25.D3	16	25	34	126	48	56				
V3100.16.5.V25.D3	16,5	25	34	129	49,5	56				
V3100.17.V25.D3	17	25	34	129	51	56				
V3100.17.5.V25.D3	17,5	25	34	132	52,5	56				
V3100.18.V25.D3	18	25	34	132	54	56				
V3100.18.5.V25.D3	18,5	25	34	135	55,5	56				
V3100.19.V25.D3	19	25	34	135	57	56				
V3100.19.5.V25.D3	19,5	25	34	139	58,8	56				
V3100.20.V25.D3	20	25	34	139	60	56				
V3100.20.5.V25.D3	20,5	25	34	143	61,5	56	WPMT 043208 (1,2 Nm)	TMSV-M2,5x7		
V3100.21.V25.D3	21	25	34	143	63	56				
V3100.21.5.V25.D3	21,5	25	34	147	64,5	56				
V3100.22.V25.D3	22	25	34	147	66	56				
V3100.22.5.V25.D3	22,5	25	34	151	67,5	56				
V3100.23.V25.D3	23	25	34	151	69	56				
V3100.23.5.V25.D3	23,5	25	34	153	70,5	56				
V3100.24.V25.D3	24	25	34	153	72	56				
V3100.24.5.V25.D3	24,5	25	34	156	73,5	56				
V3100.25.V25.D3	25	25	34	156	75	56				
V3100.25.5.V25.D3	25,5	25	34	160	76,5	56	WPMT 053308 (1,9 Nm)	TMSV-M3x8	T10	
V3100.26.V25.D3	26	25	34	160	78	56				
V3100.26.5.V25.D3	26,5	25	34	164	79,5	56				
V3100.27.V25.D3	27	25	34	164	81	56				
V3100.27.5.V25.D3	27,5	25	34	168	82,5	56				
V3100.28.V25.D3	28	25	34	168	84	56				
V3100.28.5.V25.D3	28,5	25	34	172	85,5	56				
V3100.29.V25.D3	29	25	34	172	87	56				
V3100.29.5.V25.D3	29,5	25	34	172	88,5	56				

* Tolerance vrtaného otvoru + - 0,2 mm

Objednací číslo	Rozměry (mm)							VBD	Šroubek	Klíč
	D	d	d1	L	L1	L2				
V3100.30.V32.D3	30	32	44	180	90	60	WPMT 063308 (2,9 Nm)	TMSV-M3,5x10	T15	
V3100.30.5.V32.D3	30,5	32	44	184	91,5	60				
V3100.31.V32.D3	31	32	44	184	93	60				
V3100.31.5.V32.D3	31,5	32	44	188	94,5	60				
V3100.32.V32.D3	32	32	44	188	96	60				
V3100.32.5.V32.D3	32,5	32	44	192	97,5	60				
V3100.33.V32.D3	33	32	44	192	99	60				
V3100.33.5.V32.D3	33,5	32	44	192	100,5	60				
V3100.34.V32.D3	34	32	44	192	102	60				
V3100.34.5.V32.D3	34,5	32	44	200	103,5	60				
V3100.35.V32.D3	35	32	44	200	105	60				
V3100.35.5.V32.D3	35,5	32	44	204	106,5	60				
V3100.36.V32.D3	36	32	44	204	108	60				
V3100.36.5.V32.D3	36,5	32	44	208	109,5	60				
V3100.37.V32.D3	37	32	44	208	111	60				
V3100.37.5.V32.D3	37,5	32	44	212	112,5	60				
V3100.38.V32.D3	38	32	44	212	114	60				
V3100.38.5.V32.D3	38,5	32	44	216	115,5	60				
V3100.39.V32.D3	39	32	44	216	117	60				
V3100.39.5.V32.D3	39,5	32	44	220	118,5	60				
V3100.40.V32.D3	40	32	44	220	120	60	WPMT 083412 (4,3 Nm)	TMSV-M4x11		
V3100.41.V32.D3	41	32	44	223	123	60				
V3100.42.V32.D3	42	32	44	226	126	60				
V3100.43.V32.D3	43	32	44	229	129	60				
V3100.44.V32.D3	44	32	44	232	132	60				
V3100.45.V40.D3	45	40	54	245	135	70				
V3100.46.V40.D3	46	40	54	248	138	70				
V3100.47.V40.D3	47	40	54	251	141	70				
V3100.48.V40.D3	48	40	54	254	144	70				
V3100.49.V40.D3	49	40	54	257	147	70				
V3100.50.V40.D3	50	40	54	260	150	70				

Vrtáky V3100 s vyměnitelnými VBD



HLOUBKA VRTÁNÍ 2xD/3xD/4xD/5xD

Doporučené řezné podmínky

ISO	Materiál	Tvrdość HB	Vc (m/min)	Posuv (mm/ot.)				
				WPMT03	WPMT04	WPMT05	WPMT06	WPMT08
				D15,5 - D21,5	D22 - D25,5	D26 - D30	D31 - D39	D40 - D50
P	Nelegovaná ocel, žíhaná	< 180 HB	110 - 220	0,06 - 0,09	0,06 - 0,11	0,07 - 0,13	0,08 - 0,18	0,10 - 0,25
	Nízkolegovaná ocel, žíhaná	180 - 280 HB	90 - 140	0,06 - 0,09	0,06 - 0,11	0,07 - 0,13	0,08 - 0,18	0,10 - 0,25
	Vysoce legovaná a nástr., žíhaná	280 - 350 HB	70 - 120	0,05 - 0,07	0,05 - 0,09	0,06 - 0,11	0,07 - 0,14	0,08 - 0,17
M	Nerezové oceli	< 200 HB	60 - 140	0,05 - 0,09	0,05 - 0,10	0,06 - 0,13	0,07 - 0,15	0,08 - 0,18
K	Šedá litina < 1000 N/mm ²	< 350 Mpa	100 - 160	0,07 - 0,11	0,07 - 0,13	0,08 - 0,15	0,09 - 0,18	0,11 - 0,22
	Tvárná litina	< 450 Mpa	90 - 120	0,06 - 0,10	0,06 - 0,12	0,07 - 0,14	0,08 - 0,16	0,10 - 0,20
S	Vysoce legované oceli	-	25 - 50	0,03 - 0,05	0,03 - 0,06	0,04 - 0,08	0,05 - 0,10	0,06 - 0,12
H	Superslitiny	-	25 - 50	0,03 - 0,05	0,03 - 0,06	0,04 - 0,08	0,05 - 0,10	0,06 - 0,12

* Tabulka podmínek je určena pro 2xD a 3xD tělesa

Pro 4xD těleso snížit řezné podmínky o 10%

Pro 5xD těleso snížit řezné podmínky o 15%

Katalogové číslo	P	M	K	S	H
WPMT033208-M PKU35	●	●	●	○	○
WPMT033208-M PKS38	●	●	●	●	●
WPMT033208-M PKT38	●	●	●	●	●
WPMT033208-M PKS48	●	●	●	●	

Katalogové číslo	P	M	K	S	H
WPMT053308-M PKU35	●	●	●	○	○
WPMT053308-M PKS38	●	●	●	●	●
WPMT053308-M PKT38	●	●	●	●	●
WPMT053308-M PKS48	●	●	●	●	
WPMT053308-S PKU35	●	●		○	○
WPMT053308-S PKS38	●	●	●	●	●
WPMT053308-S PKT38	●	●	●	●	
WPMT053308-S PKS48	●	●	●	●	

Katalogové číslo	P	M	K	S	H
WPMT083412-M PKU35	●	●	●	○	○
WPMT083412-M PKS38	●	●	●	●	●
WPMT083412-M PKT38	●	●	●	●	●
WPMT083412-M PKS48	●	●	●	●	
WPMT083412-S PKU35	●	●	●	○	○
WPMT083412-S PKS38	●	●	●	●	●
WPMT083412-S PKT38	●	●	●	●	●
WPMT083412-S PKS48	●	●	●	●	


● = 1.volba doporučené ○ = 2.volba vhodné

Katalogové číslo	P	M	K	S	H
WPMT043208-M PKU35	●	●	●	○	○
WPMT043208-M PKS38	●	●	●	●	●
WPMT043208-M PKT38	●	●	●	●	●
WPMT043208-M PKS48	●	●	●	●	
WPMT043208-S PKU35	●	●	●	○	○
WPMT043208-S PKS38	●	●	●	●	●
WPMT043208-S PKT38	●	●	●	●	●
WPMT043208-S PKS48	●	●	●	●	

Katalogové číslo	P	M	K	S	H
WPMT063308-M PKU35	●	●	●	○	○
WPMT063308-M PKS38	●	●	●	●	●
WPMT063308-M PKT38	●	●	●	●	●
WPMT063308-M PKS48	●	●	●	●	
WPMT063308-S PKU35	●	●	●	○	○
WPMT063308-S PKS38	●	●	●	●	●
WPMT063308-S PKT38	●	●	●	●	●
WPMT063308-S PKS48	●	●	●	●	

Rozměry (mm)

VBD	A	B	S	r	d1
WPMT 033208	3,8	5,56	2,38	0,8	2,8
WPMT 043208	4,3	6,35	2,38	0,8	3
WPMT 053308	5,4	7,94	3,18	0,8	3,4
WPMT 063308	6,5	9,53	3,97	0,8	4
WPMT 083412	8,7	12,7	4,76	1,2	4,3



Tvar bříty



ostrá geometrie, lehká tvorba třísky

Tvar bříty



nízké řezné síly během obrábění