


Upínač Weldon s chladícími kanály pro upínací stopky



Upínač Weldon DIN 6359 pro upínací stopky DIN 1835-B



Název	Kužel	D	d	A	G 2,5 25.000 min ⁻¹
C6.55.WK.06	C6	25	6	55	•
C6.55.WK.08	C6	28	8	55	•
C6.60.WK.10	C6	35	10	60	•
C6.60.WK.12	C6	42	12	60	•
C6.60.WK.14	C6	44	14	60	•
C6.65.WK.16	C6	48	16	65	•
C6.65.WK.18	C6	50	18	65	•
C6.65.WK.20	C6	52	20	65	•
C6.80.WK.25	C6	65	25	80	•
C6.90.WK.32	C6	72	32	90	•
C6.100.WK.40	C6	80	40	100	•
C6.100.WK.06	C6	25	6	100	•
C6.100.WK.08	C6	28	8	100	•
C6.100.WK.10	C6	35	10	100	•
C6.100.WK.12	C6	42	12	100	•
C6.100.WK.14	C6	44	14	100	•
C6.100.WK.16	C6	48	16	100	•
C6.100.WK.20	C6	52	20	100	•
C6.160.WK.06	C6	25	6	160	•
C6.160.WK.08	C6	28	8	160	•
C6.160.WK.10	C6	35	10	160	•
C6.160.WK.12	C6	42	12	160	•
C6.160.WK.16	C6	48	16	160	•

od průměru d = 25 se dvěma upínacími šrouby

d = 6 až 18 se dvěma chladícími kanály

d = 20 až 40 se čtyřmi chladícími kanály