


Redukční pouzdro HSK/PSC




redukce z HSK-A (ISO 12164) na Capto (ISO 26623-1)



Název	Kužel	Typ	D	A	Doporučený utahovací moment Nm	G 6,3 15.000 min ⁻¹
HSK63A.75.R.C3	HSK63	C3	32	75	45	•
HSK63A.80.R.C4	HSK63	C4	40	80	55	•
HSK63A.90.R.C5	HSK63	C5	50	90	95	•
HSK100A.80.R.C3	HSK100	C3	32	80	45	•
HSK100A.90.R.C4	HSK100	C4	40	90	55	•
HSK100A.100.R.C5	HSK100	C5	50	100	95	•
HSK100A.110.R.C6	HSK100	C6	63	110	170	•

redukce z HSK-T (ISO 12164-3) na Capto (ISO 26623-1)



Název	Kužel	Typ	D	A	Doporučený utahovací moment Nm	G 6,3 15.000 min ⁻¹
HSK63T.75.R.C3	HSK63	C3	32	75	45	•
HSK63T.80.R.C4	HSK63	C4	40	80	55	•
HSK63T.90.R.C5	HSK63	C5	50	90	95	•
HSK63T.110.R.C6	HSK63	C6	63	110	170	•
HSK100T.80.R.C3	HSK100	C3	32	80	45	•
HSK100T.90.R.C4	HSK100	C4	40	90	55	•
HSK100T.100.R.C5	HSK100	C5	50	100	95	•
HSK100T.110.R.C6	HSK100	C6	63	110	170	•