


Upínač pro nástrčné frézy - kombi

DIN 6358



Název	Kužel	d	D	A	l ₁	l ₂	G 6,3 15.000 min ⁻¹
ISO30.35.NK.16.AD	ISO30	16	32	35	17	27	•
ISO30.35.NK.22.AD	ISO30	22	40	35	19	31	•
ISO30.35.NK.27.AD	ISO30	27	48	35	21	33	•
ISO30.50.NK.32.AD	ISO30	32	58	50	24	38	•
ISO40.52.NK.16.AD	ISO40	16	32	52	17	27	•
ISO40.52.NK.22.AD	ISO40	22	40	52	19	31	•
ISO40.52.NK.27.AD	ISO40	27	48	52	21	33	•
ISO40.52.NK.32.AD	ISO40	32	58	52	24	38	•
ISO40.52.NK.40.AD	ISO40	40	70	52	27	41	•
ISO50.55.NK.16.AD	ISO50	16	32	55	17	27	•
ISO50.55.NK.22.AD	ISO50	22	40	55	19	31	•
ISO50.55.NK.27.AD	ISO50	27	48	55	21	33	•
ISO50.55.NK.32.AD	ISO50	32	58	55	24	38	•
ISO50.55.NK.40.AD	ISO50	40	70	55	27	41	•

dodávka: s upínacím šroubem, unášecím kroužkem a perem