


Upínač Weldon pro upínací stopky



Upínač Weldon DIN 6359 pro upínací stopky DIN 1835-B



Název	Kužel	D	d	A	G 6,3 15.000 min ⁻¹
ISO30.40.WE.06	ISO30	25	6	40	•
ISO30.40.WE.08	ISO30	28	8	40	•
ISO30.40.WE.10	ISO30	35	10	40	•
ISO30.40.WE.12	ISO30	42	12	40	•
ISO30.50.WE.14	ISO30	44	14	50	•
ISO30.50.WE.16	ISO30	48	16	50	•
ISO30.50.WE.18	ISO30	50	18	50	•
ISO30.63.WE.20	ISO30	52	20	63	•
ISO40.50.WE.06	ISO40	25	6	50	•
ISO40.50.WE.08	ISO40	28	8	50	•
ISO40.50.WE.10	ISO40	35	10	50	•
ISO40.50.WE.12	ISO40	42	12	50	•
ISO40.50.WE.14	ISO40	44	14	50	•
ISO40.63.WE.16	ISO40	48	16	63	•
ISO40.63.WE.18	ISO40	50	18	63	•
ISO40.63.WE.20	ISO40	52	20	63	•
ISO40.80.WE.25	ISO40	65	25	80	•
ISO40.80.WE.32	ISO40	72	32	80	•
ISO40.90.WE.40	ISO40	80	40	90	•
ISO50.63.WE.06	ISO50	25	6	63	•
ISO50.63.WE.08	ISO50	28	8	63	•
ISO50.63.WE.10	ISO50	35	10	63	•
ISO50.63.WE.12	ISO50	42	12	63	•
ISO50.63.WE.14	ISO50	44	14	63	•
ISO50.63.WE.16	ISO50	48	16	63	•
ISO50.63.WE.18	ISO50	50	18	63	•
ISO50.63.WE.20	ISO50	52	20	63	•
ISO50.80.WE.25	ISO50	65	25	80	•
ISO50.80.WE.32	ISO50	72	32	80	•
ISO50.90.WE.40	ISO50	80	40	90	•

od průměru 25 se dvěma upínacími šrouby